



Dutch Boy

Kem-Tone

Technical Data Sheet

021/TDS/SCI/VIII/2019



www.sci-paint.com

3 in 1 Primer/Sealer

3 in 1 Primer/Sealer

High quality exterior acrylic primer (under coater).



Features:

- Alkali resistant
- Stain blocking primer/sealer
- Breathing film without adhesion loss from the substrate
- Can be used to prime marginally cured concrete
- Used under latex or oil (solvent based paints)
- Use thinner ND or thinner super

Description:

High quality exterior acrylic primer (under coater). It is highly alkali and efflorescence resistant. Can be used to block most stain. Recommended for interior and exterior.

Typical Uses:

Recommended for exterior, above-grade masonry surfaces. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc.

Characteristics:

Vehicle Type

Finish

Colors

Weight/liter

Solids

Viscosity

Drying Time (to touch)*

Drying Time (to recoat)*

* @ 25°C & 50% R.H.

Coverage

Tinting

: Acrylic (solvent-based)

: Flat, 0-10 units @ 85°

: White

: 1.30 - 1.40 Kg/liter

: Volume 59 - 61 %

: 81 - 85.2 KU

: 20 - 30 minutes

: 4 - 8 hours

: 45 - 50 m² per-gallon (substrate dependent)

: Not Available

Application:

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



Dutch Boy

Kem-Tone

Technical Data Sheet

021/TDS/SCI/VIII/2019



www.sci-paint.com

Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not store paint in an upside down position.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This oil-based paint and keep it away from fire, because it is flammable.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Clean all paint equipment or supplies after painting.
- Do not breathe product or spray directly.
- Use a nose mask to paint.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: info@sci-paint.com; Website: www.sci-paint.com

