



scipaint

Spectrum® **UltraPrimer**

Technical Data Sheet

012/TDS/SCI/VIII/2019



www.sci-paint.com

DESCRIPTION

A high performance water based primer designed to protect the finish against alkali, chalking, and efflorescence.

FEATURES

- Water-Based
- Maximum Protection against alkali and moisture
- Adding Paint Adhesion and Maximum Durability
- Excellent Adhesion
- Weather Resistance

TYPICAL USES

Recommended for walls. Use on wallboard or drywall, primed plaster, concrete, brick, and wallpaper. Uses in homes, schools, offices, hospitals, condominiums, commercial properties, etc. For interior and exterior applications.

CHARACTERISTICS

Vehicle Type	: Acrylic
Finish	: Satin
Colors	: White
Weight/liter	: 1.17-1.19 Kg/liter
Solids	: Volume 46-48%, Weight: 54 - 56%
Viscosity	: 88-95 KU
pH	: 8.5-9.0
Drying Time (to touch)*	: 3-4 hours
Drying Time (to recoat)*	: 4 hours
*@25°C & 50% R.H.	
Cured Time	: 24 hours
Coverage	: 25-30 m ² /gallon (one coat application)

APPLICATION

Use roll, brush or airless spray. Paint at temperature above 10°C. Protect from freezing.



scipaint

Spectrum® **UltraPrimer**

Technical Data Sheet

012/TDS/SCI/VIII/2019



www.sci-paint.com

Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not hang paint can on the can hook.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This paint is water based and does not use epoxy based ingredients.
- Free of hazardous chemicals and have very low levels of VOC and odor.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Wash all equipment or supplies with clean water after painting.
- Do not breathe product or spray directly.
- Use a nose mask when flattening walls, removing old paint and when painting.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: info@sci-paint.com; Website: www.sci-paint.com

