



scipaint



Dutch Boy

# Kem-Tone

## Technical Data Sheet

027/TDS/SCI/VIII/2019



www.sci-paint.com

### Technique Glaze

#### Features:

The easy way to add depth and beauty to any room

- Tintable clear technique glaze
- Available in 40 colors, or mix directly with paint
- Add riches to any wall



#### Description:

Kem-Tone Technique Glaze is rich, translucent, and mixed with paint to create custom faux-finishing looks. It allows the undercoat to show through and extends the drying time to give you more minutes to work painting techniques. Designed to mix a ratio of four parts glaze to one part paint, Kem-Tone Technique Glaze is available in one-quart and one-gallon sizes.

#### What is it?

Kem-Tone Technique Glaze is a beautifully translucent finish that adds depth to all faux finishing and decorative painting techniques.

#### Why use it?

Glaze gives you more working time when applying techniques. With Kem-Tone Technique Glaze, you have up to 20 minutes before it dries, depending on temperature and humidity. Plus, glaze beautifully retains the patterns left by the tools used to apply it.

#### How much do I need?

You can cover between 40 and 80 m<sup>2</sup> with a gallon of Kem-Tone Technique Glaze, depending on your chosen technique.

#### What tools work best?

There are many tools and materials you can use to create terrific techniques with glaze.

Sponges, lint-free rags, brushes, rollers, combs, and even plastic bags can be used to create unique decorative finishes.



scipaint



Dutch Boy

# Kem-Tone

## Technical Data Sheet

027/TDS/SCI/VIII/2019



www.sci-paint.com

### Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not hang paint can on the can hook.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

### Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This paint is water based and does not use epoxy based ingredients.
- Free of hazardous chemicals and have very low levels of VOC and odor.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Wash all equipment or supplies with clean water after painting.
- Do not breathe product or spray directly.
- Use a nose mask when flattening walls, removing old paint and when painting.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



### COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: [info@sci-paint.com](mailto:info@sci-paint.com); Website: [www.sci-paint.com](http://www.sci-paint.com)

