



scipaint

Spectrum[®] LUXURIOUS TEXTURE GRANITE

Technical Data Sheet

001/TDS/SCI/VI/2021



www.sci-paint.com

DESCRIPTION

Spectrum Granite is a special water-based paint that is specially formulated to create a weather-resistant granite effect on the painted surface. Spectrum Granite is suitable for both interior and exterior use.

FEATURES

- Excellent adhesion strength
- Easy application and workability
- Due to chemical structure, excellent against contamination
- Usage of stabilized color aggregates
- Good color retention
- Excellent water and weather resistance
- Economical compared

TYPICAL USES

Suitably primed surfaces of concrete, mortar, masonry, soft and hard boards, wood, gypsum plaster board, metal surfaces, etc. Use in homes, schools, offices, hospitals, condominiums, commercial properties, etc. Interior and exterior

CHARACTERISTICS

Resin Type	: Acrylic Latex
Finish	: Textured
Colors	: Standard color in Spectrum Granite catalogue
Specific Gravity	: 1.80 ± 0.05
Drying Time (At 30°C)	
Surface Dry	: 1 hour
Hard Dry	: 24 hours
Film Thickness	
Dry Film (Theoretical)	: Depend on choice of color
Solid Content	: 81 ± 3%
Viscosity	: 360 ± 100ps/30°C
Coverage	: 1.2Kg/m ² (substrate dependent)

APPLICATION

Only use airless spray. Paint at temperature above 10°C. Protect from freezing.



scipaint

Spectrum[®] LUXURIOUS TEXTURE GRANITE

Technical Data Sheet

001/TDS/SCI/VI/2021



www.sci-paint.com

Storage Instruction:

- Paint can must always be tightly closed and keep away from children.
- Keep away from food, drinks and animal food because it is dangerous if swallowed.
- Paint can only can be used to store paint.
- Store paint in a cool and dry place.
- Do not hang paint can on the can hook.
- Keep the paint can standing.
- After used, close the lid tightly before storing.

Information on safety, security, health work and environment:

- This paint does not contain: mercury, lead, formalin and cadmium.
- This paint is water based and does not use epoxy based ingredients.
- Free of hazardous chemicals and have very low levels of VOC and odor.
- During the painting and drying process must be ensured in a well ventilated area.
- Recommended to use eye protector during painting.
- If in contact with eyes, rinse with clean water, if necessary consult a doctor.
- You should also use gloves during painting.
- Stir the paint with tools, do not use hand directly.
- Wash or clean the paint on the skin with soap and water.
- Wash all equipment or supplies with clean water after painting.
- Do not breathe product or spray directly.
- Use a nose mask when flattening walls, removing old paint and when painting.
- Do not throw the rest of the paint into gutter or creeks to keep the environment clean.
- Dispose of the remaining paint in a place that has been permitted according to existing regulations.
- If the paint spills, sprinkle sand or soil on the spilled area then clean.



COMPANY NAME

PT. SAN CENTRAL INDAH (SCI PAINT)

Jl. Raya Batujajar Km. 3,5 Padalarang 40561, Bandung-Indonesia.

Telp: (+62-22) 686 6128 (7 lines); Fax: (+62-22) 686 6124;

Email: info@sci-paint.com; Website: www.sci-paint.com

